




BMW i12

Coupé

(06/2014 – 11/2015)



Legend

	Airbag		Stored gas inflator		Seat belt pretensioner		SRS control unit		Pedestrian protection active system
	Automatic rollover protection system		Gas strut / Preloaded spring		High strength zone		Zone requiring special attention		High voltage disconnect (cutting solution)
	Battery low voltage		Ultra capacitor, low voltage		Fuel tank		Gas tank		Safety valve
	High voltage battery pack		High voltage power cable / component		High voltage disconnect		Fuse box disabling high voltage system		Ultra capacitor, high voltage

This overview shows the maximum range of equipment of the vehicle

	ID no.	Version no.	Version date	Page
	WBY-I12	1	06/2014	01

Important: For more information see rescue manual.

© 2016 BMW AG Munich, Germany

DANGER

High voltage system.

The high voltage system carries high voltage currents. Fatal electric shock hazard!

- Do not touch the high voltage battery.

Secure the vehicle to prevent it from rolling away

Press button "P" (1). Pull the switch (2) for the electric parking brake upward.



Deactivate the drive and high voltage system (set to de-energised condition) - airbag not deployed (START-STOP and low voltage battery accessible)

i TECHNICAL INFORMATION

In case of accidents resulting in airbag deployment, the high voltage system is automatically deactivated (de-energised).


i TECHNICAL INFORMATION

The negative terminal of the low voltage battery and the high voltage disconnect must be disconnected in all cases.

If the engine is running or displays are active in the instrument cluster, press the "START STOP" button to switch off the ignition.




Open the bonnet. Unlock the plug for high voltage disconnect (1) and pull apart in the direction of the arrow.



The high voltage system is deactivated when the hole (1) is clear all the way through and the word "OFF" can be seen on the plug.


To avoid inadvertent activation of the high voltage system, a padlock can be installed through the open hole (1), for example!

Note: The plug connection cannot be completely separated.



Loosen nut (1) and pull off battery negative cable (2) upwards.

Cover the battery negative terminal to exclude any contact with the battery negative cable.



Labelling of the high voltage components

The high voltage battery is located on the vehicle floor.

Labelling of the high voltage battery pack:



Labelling of the remaining high voltage components:



Identification of the high voltage cables (1) (insulation / orange sheath):

